

**Made in America**

**Lifetime Guarantee**



**Thank you for purchasing this installation kit from Intellitronix. We value our customers!**

### **INSTALLATION GUIDE**

**LS Engine Swap Adapter Kit**

**Part Number: 8014LS**

**\* Always disconnect the battery *before* attempting any electrical work on your vehicle.\***



#### **Kit Components:**

- ◇ One (1) Bushing 1/8" NPT to 12 mm for water temperature sender
- ◇ One (1) Bushing 1/8" NPT to 16 mm for oil pressure sender
- ◇ One resistor for tachometer connection

### **INSTRUCTIONS**

***Note: Automotive circuit connectors are the preferred method of connecting wires. However, you may solder if you prefer.***

1. Insert 12 mm bushing into the port located on the rear of the right side cylinder head. Then, insert temperature sender into bushing and complete wiring.
2. Insert 16 mm bushing into the port on the engine block, which is usually located near the oil filter. Then insert oil pressure sender into bushing and complete wiring.
3. If the tachometer does not work, you will need to install the enclosed resistor. It should be inserted between the green wire from the tachometer and the (red) 12v Ignition Wire.
4. The connections for the resistor may be soldered at each end.

**Be sure to test for leaks before driving the vehicle.**

Made in America

Lifetime Guarantee



Technical Support

Monday – Friday

9am to 5 pm EST

(440) 210-7646

[support@intellitronix.com](mailto:support@intellitronix.com)



**This product carries a limited Lifetime Warranty.**

**This warranty is limited to replacement or repair of the unit at the discretion of Intellitronix.**